

AMENDMENTS TO THE CLAIMS:

This listing of claims will replace all prior versions, and listings, of claims in the application:

LISTING OF CLAIMS:

1. (previously presented) A system of lifting and conveying a concrete slab and any associated works, wherein the slab has a plurality of apertures therethrough the slab area, the said apertures being provided with a respective jack, said jack at least comprising at least one shaft having a portion passing through said aperture and contacting a lower support means, means for connecting said slab to said shaft, the connection means incorporating at least one supporting member connecting the slab to the shaft, each supporting member passing through another said aperture and engaging said slab, and means for effecting

longitudinal travel of a supporting means along said shaft, otherwise resulting in the raising or lowering of said slab, position sensors associated with each jack, means for communicating between each jack and one or more main controllers, and means for controlling each jack whereby the jacks are movable in a synchronised manner,

wherein each shaft comprises a pair of columns on either side of a ball screw, the ball screw being supported by a spherical roller bearing mounted in a top plate, thus bridging the columns.

2. (original) A system as claimed in claim 1 wherein the jack includes trailing restraint means being adapted to provide restraint and or stability for the jack once it has climbed or the jack has been disconnected from the slab.

3. (original) A system as claimed in claim 2 wherein each aperture therein containing the supporting member is provided in co-operation with the position of the shaft, and henceforth the aperture through which it passes.

4. (original) A system as claimed in claim 3 wherein said lower supporting means includes a supporting strut supporting the shaft from the floor below.

5. (original) A system as claimed in claim 4 wherein said lower supporting means includes a back prop supporting the floor below the strut.

6. (original) A system as claimed in claim 5 wherein each aperture therein containing said shaft is proportionally larger in diameter than said aperture therein containing said supporting member.

7. (original) A system as claimed in claim 6 wherein each supporting member engages with the downwardly facing or upper face of the slab.

8. (original) A system as claimed in claim 7 wherein each jack has pivoting means such that in use each jack can accommodate displacement of the jack whereby there is a minimum transfer of moment through any tensile members.

9. (cancelled)

10. (previously presented) A system as claimed in claim 1 wherein hanger rods are steel rods adapted to connect a hanger assembly to the slab.

11. (original) A system as claimed in claim 10 wherein the hanger rods are provided with a respective sleeve.

12. (original) A system as claimed in claim 11 wherein the connection means comprises a hanger assembly in co-operation with at least one supporting member.

13. (original) A system as claimed in claim 12 wherein the supporting member/s are provided with bearing plates on the underside of the slab, and connected by corresponding bearing plates and fasteners to the hanger assembly.

14. (original) A system as claimed in claim 13 wherein the hanger assembly is supported for movement along said shaft, and more preferably the hanger assembly is pivotally supported at a point of rotation at some point along the central axis of the ball screw.

15. (original) A system as claimed in claim 14 wherein during climbing, the ball screw will turn downwards in the opposite direction from when it is lifting the slab.

16. (original) A system as claimed in claim 15 wherein during climbing the hanger acts in compression and during lifting of each slab, the hanger is in tension.

17. (original) A system as claimed in claim 16 wherein during climbing the ball screw acts in tension while during lifting the ball screw acts in compression.

18. (original) A system as claimed in claim 17 wherein the means for communicating between each jack includes a wire and wireless means.

19. (original) A system as claimed in claim 18 wherein a micro processor or computer or PLC or in combination, is connected via an electric motor to each jack such that synchronised position control is achieved for all the jacks.

20. (original) A system as claimed in claim 19 wherein each jack includes a jack driven by the electric or hydraulic motor which is controlled by a variable speed drive.

21. (original) A system as claimed in claim 20 wherein the system includes a scaffolding means, said scaffolding means adapted to associate with and accompany the concrete slab, wherein said scaffolding means comprises a platform, said platform adapted to engage with a shaft, said platform adapted to allow a number of persons to stand thereon; said shaft therein passing through a guiding means, said guiding means connected to a material to be lifted; a connection means therein adapted to connect the shaft with the material to be lifted.

22. (cancelled)

23. (previously presented) A method of lifting a concrete slab and associated works, wherein there is provided a concrete slab having an area having a plurality of apertures therethrough, a number of said apertures provided with a respective jack, said jack at least comprising at least one shaft having a portion passing through said aperture and contacting a lower support means, means for connecting said slab to said shaft, the connection means incorporating at least one supporting member connecting the slab to the shaft, each supporting member passing through another said aperture and engaging said slab, and means for effecting longitudinal travel of said supporting means along said shaft, otherwise resulting in the raising or lowering of said slab, position sensors associated with each jack, means for communicating between each jack and one or more main controllers, and means for controlling each jack wherein the method includes the following steps of:

connecting at least one jack to a slab;

connecting communication means to at least one jack;

connecting at least one controller to the jack via the communication means;

activating the control means whereby each jack is preloaded followed by further activating the control means to each jack in a co-ordinated or synchronised manner whereby the slab is raised/lowered by a specific amount,

wherein each shaft comprises a pair of columns on either side of a ball screw, the ball screw being supported by a spherical roller bearing mounted in a top plate, thus bridging the columns.

24-26. (cancelled)

27. (currently amended) A jack as claimed in claim ~~26~~ 23 wherein the support device includes a trailing restraint member being arranged with the shaft whereby the trailing restraint member is removably located and connected with the shaft such that in use it can be fully extended from the shaft when the jack has climbed.

28. (original) A jack as claimed in claim 27 wherein a strut member is linked to the shaft such that when the jack is climbed, the strut can be raised with the jack to the next floor, to provide support for the jack to the floor below the jack.

29. (original) A jack as claimed in claim 28 wherein the strut is provided with a removable foot member, to redistribute any strut loading through the slab in the floor below the jack.

30-40. (cancelled)